





LED

**Full Color ϕ 3mm
Columniation LED**

FEATURES:

- Viewing angle 120°
- For LED Screen
- UV resistant epoxy



Absolute Max Ratings (Ta=25°C):

Parameter	Symbol	Value	
		Green / Blue	Red
Power Dissipation (mW)	PD	100	125
DC Forward Current (mA)	IF	30	50
Pulsed Forward Current* (mA)	IFP	100	150
Reverse Voltage (V)	VR	5	5
Operating Temperature (°C)	Topr	-30 ~ +80	
Storage Temperature (°C)	Tstg	-40 ~ +100	

* Duty 1/10 Pulse Width 0.1ms


Electrical Optical Characteristics (Ta=25°C):

Part Number	Luminous Intensity (mcd)			Forward Voltage (V)			Dominant Wavelength (nm)			Reverse Current (μA)	
	Min	Max	IF(mA)	Type	Max	IF(mA)	Min	Max	IF(mA)	Max	VR(V)
C03URDQ-S1	100	170	20	2.0	2.2	20	620	625	20	5	5
							625	630			
C03FDQ-S1	300	535	20	3.2	3.6	20	520	525	20	10	5
							525	530			
C03BDQ-S1	130	230	20	3.2	3.6	20	465	470	20	10	5
							470	475			

Luminous Intensity Rank (mcd)

Red		Green		Blue	
Rank	Data	Rank	Data	Rank	Data
A	100-130	E	300-400	B	130-170
A1	115-150	E1	350-460	B1	150-200
B	130-170	F	400-535	C	170-230

Directive Characteristics



Package:

Bulk: 500 pcs/bag

Taping: 3,000 pcs/reel

Precaution in handling:

1. It is advised to keep 5.0mm minimum clearance between the resin and the soldering point when soldering.
2. The user is required to handle with care for the Blue and Green LED's which are sensitive to ESD.