



METALIZED POLYESTER FLIM CAPACITOR

TYPE MER

DIMENSIONS:

(unit: mm)

W.V.	50V/63V DC					100V DC					250V DC				
Cap(μ F)	W	H	T	P	d ϕ	W	H	T	P	d ϕ	W	H	T	P	d ϕ
0.01	10.5	9.0	5.0	7.5	0.6	14.0	10.0	6.0	10.0	0.6	14.0	10.0	6.0	10.0	0.6
0.015	10.5	9.5	6.0	7.5	0.6	14.0	11.5	6.5	10.0	0.6	14.0	11.5	6.5	10.0	0.6
0.022	10.5	9.5	6.0	7.5	0.6	14.0	11.0	7.0	10.0	0.6	14.0	11.0	7.0	10.0	0.6
0.033	10.5	9.5	6.0	7.5	0.6	14.0	11.5	7.0	10.0	0.6	14.0	11.5	7.0	10.0	0.6
0.047	10.5	9.5	6.0	7.5	0.6	14.0	11.5	7.0	10.0	0.6	14.0	11.5	7.0	10.0	0.6
0.068	10.5	9.5	6.0	7.5	0.6	14.0	11.5	7.0	10.0	0.6	14.0	11.5	7.0	10.0	0.6
0.1	10.5	9.5	6.0	7.5	0.6	14.0	10.0	6.0	10.0	0.6	14.0	10.0	7.0	10.0	0.6
0.15	10.5	10.5	7.0	7.5	0.6	14.0	10.0	6.0	10.0	0.6	14.0	12.0	8.0	10.0	0.6
0.22	10.5	10.5	7.0	7.5	0.6	14.0	10.5	6.5	10.0	0.6	19.0	12.0	8.0	15.0	0.6
0.33	10.5	11.0	8.0	7.5	0.6	14.0	11.5	8.5	10.0	0.6	19.0	13.0	8.0	15.0	0.6
0.47	10.5	11.5	8.0	7.5	0.6	19.0	12.0	7.0	15.0	0.6	19.0	15.0	8.0	15.0	0.8
0.68	13.0	11.5	7.0	10.0	0.6	19.0	14.0	7.5	15.0	0.6	24.0	15.5	9.0	20.0	0.8
1.0	13.0	12.5	7.0	10.0	0.6	19.0	15.0	8.5	15.0	0.8	24.0	17.0	10.0	20.0	0.8
1.5	18.5	14.0	8.0	15.0	0.8	24.0	17.0	9.0	20.0	0.8	24.0	21.0	11.50	20.0	0.8
2.2	18.5	15.0	10.0	15.0	0.8	24.0	20.0	9.0	20.0	0.8	32.0	22.0	13.0	27.5	0.8
3.3						24.0	20.0	12.0	20.0	0.8	32.0	26.0	16.0	27.5	0.8
4.7						32.0	22.0	13.0	27.5	0.8	35.0	23.0	15.0	31.0	0.8
6.8						32.0	26.0	16.0	27.5	0.8					
10.0						32.0	31.0	18.0	27.5	0.8					

W.V.	400V DC					630V DC				
Cap.(μ F)	W	H	T	P	d ϕ	W	H	T	P	d ϕ
0.01	14.0	10.0	6.0	10.0	0.6	14.0	10.0	6.0	10.0	0.6
0.015	14.0	11.5	6.5	10.0	0.6	14.0	11.5	6.5	10.0	0.6
0.022	14.0	11.0	7.0	10.0	0.6	14.0	12.5	7.0	10.0	0.6
0.033	14.0	11.5	7.0	10.0	0.6	14.0	13.5	9.0	10.0	0.6
0.047	14.0	11.5	7.0	10.0	0.6	19.0	12.5	7.5	15.0	0.6
0.068	19.0	13.0	6.0	15.0	0.6	19.0	14.5	9.0	15.0	0.8
0.1	19.0	13.0	7.0	15.0	0.6	19.0	15.5	9.5	15.0	0.8
0.15	19.0	14.0	7.5	15.0	0.8	24.0	17.0	10.0	20.0	0.8
0.22	19.0	16.0	10.0	15.0	0.8	24.0	20.0	11.0	20.0	0.8
0.33	24.0	16.0	10.0	20.0	0.8	24.0	22.0	13.0	20.0	0.8
0.47	24.0	18.5	11.0	20.0	0.8	32.0	22.0	13.0	27.5	0.8
0.68	32.0	18.5	11.5	27.5	0.8	35.0	26.0	15.0	31.0	0.8
1.0	32.0	22.0	12.0	27.5	0.8	35.0	30.0	17.0	31.0	0.8
1.5	32.0	24.0	14.0	27.5	0.8					
2.2	35.0	24.5	15.0	31.0	0.8					
3.3	35.0	30.0	18.0	31.0	0.8					
4.7	41.0	31.0	19.0	36.0	0.8					