



METALIZED POLYESTER FLIM CAPACITOR

TYPE MER (P=5.0)

DIMENSIONS:

(unit: mm)

W.V.	50V DC			63V DC			100V DC		
Cap.(μ F)	W	H	T	W	H	T	W	H	T
0.001	7.0	6.5	4.0	7.0	6.5	4.0	7.0	6.5	4.0
0.0012	7.0	6.5	4.0	7.0	6.5	4.0	7.0	6.5	4.0
0.0015	7.0	6.5	4.0	7.0	6.5	4.0	7.0	6.5	4.0
0.0018	7.0	6.5	4.0	7.0	6.5	4.0	7.0	6.5	4.0
0.0022	7.0	6.5	4.0	7.0	6.5	4.0	7.0	6.5	4.0
0.0027	7.0	6.5	4.0	7.0	6.5	4.0	7.0	6.5	4.0
0.0033	7.0	6.5	4.0	7.0	6.5	4.0	7.0	6.5	4.0
0.0039	7.0	6.5	4.0	7.0	6.5	4.0	7.0	6.5	4.0
0.0047	7.0	6.5	4.0	7.0	6.5	4.0	7.0	6.5	4.0
0.0056	7.0	6.5	4.0	7.0	6.5	4.0	7.0	6.5	4.0
0.0068	7.0	6.5	4.0	7.0	6.5	4.0	7.0	6.5	4.0
0.0082	7.0	6.5	4.0	7.0	6.5	4.0	7.0	6.5	4.0
0.01	7.0	6.5	4.0	7.0	6.5	4.0	7.0	6.5	4.0
0.012	7.0	6.5	4.0	7.0	6.5	4.0	7.0	6.5	4.0
0.015	7.0	6.5	4.0	7.0	6.5	4.0	7.0	6.5	4.0
0.018	7.0	6.5	4.0	7.0	6.5	4.0	7.0	6.5	4.0
0.022	7.0	6.5	4.0	7.0	6.5	4.0	7.0	7.0	4.0
0.027	7.0	6.5	4.0	7.0	6.5	4.0	7.0	7.0	4.0
0.033	7.0	6.5	4.0	7.0	6.5	4.0	7.0	7.0	4.0
0.039	7.0	6.5	4.0	7.0	6.5	4.0	7.0	7.0	4.0
0.047	7.0	6.5	4.0	7.0	6.5	4.0	7.0	7.0	4.0
0.056	7.0	6.5	4.0	7.0	6.5	4.0	7.0	7.0	4.0
0.068	7.0	6.5	4.0	7.0	6.5	4.0	7.0	8.0	4.5
0.082	7.0	6.5	4.0	7.0	6.5	4.0	7.0	9.0	5.0
0.1	7.0	6.5	4.0	7.0	6.5	4.0	7.0	9.0	5.0
0.12	7.0	6.5	4.0	7.0	6.5	4.0			
0.15	7.0	7.0	4.5	7.0	7.0	4.5			
0.18	7.0	7.0	4.5	7.0	7.0	4.5			
0.22	7.0	7.0	4.5	7.0	8.0	4.5			
0.27	7.0	8.0	4.5	7.0	8.0	4.5			
0.33	7.0	8.0	4.5	7.0	9.0	5.0			
0.39	7.0	9.0	4.5						
0.47	7.0	9.0	4.5						