



# METALIZED POLYESTER FLIM CAPACITOR

## TYPE MER (P=7.5)

### DIMENSIONS:

(unit: mm)

W.V.	50V / 63V DC			100V DC			250V DC		
CAP.( $\mu$ F)	W	H	T	W	H	T	W	H	T
0.001	10.0	7.0	4.0	10.0	7.0	4.0	10.0	7.0	4.0
0.0012	10.0	7.0	4.0	10.0	7.0	4.0	10.0	7.0	4.0
0.0015	10.0	7.0	4.0	10.0	7.0	4.0	10.0	7.0	4.0
0.0018	10.0	7.0	4.0	10.0	7.0	4.0	10.0	7.0	4.0
0.0022	10.0	7.0	4.0	10.0	7.0	4.0	10.0	7.0	4.0
0.0027	10.0	7.0	4.0	10.0	7.0	4.0	10.0	7.0	4.0
0.0033	10.0	7.0	4.0	10.0	7.0	4.0	10.0	7.0	4.0
0.0039	10.0	7.0	4.0	10.0	7.0	4.0	10.0	7.0	4.0
0.0047	10.0	7.0	4.0	10.0	7.0	4.0	10.0	7.0	4.0
0.0056	10.0	7.0	4.0	10.0	7.0	4.0	10.0	7.0	4.0
0.0068	10.0	7.0	4.0	10.0	7.0	4.0	10.0	7.0	4.0
0.0082	10.0	7.0	4.0	10.0	7.0	4.0	10.0	7.0	4.0
0.01	10.0	7.0	4.0	10.0	7.0	4.0	10.0	7.0	4.0
0.012	10.0	7.0	4.0	10.0	7.0	4.0	10.0	7.0	4.0
0.015	10.0	8.0	4.5	10.0	8.0	4.5	10.0	8.0	4.5
0.018	10.0	8.0	4.5	10.0	8.0	4.5	10.0	8.0	4.5
0.022	10.0	8.0	4.5	10.0	8.0	4.5	10.0	8.0	4.5
0.027	10.0	8.0	4.5	10.0	8.0	4.5	10.0	8.0	4.5
0.033	10.0	8.0	4.5	10.0	8.0	4.5	10.0	8.0	4.5
0.039	10.0	8.0	4.5	10.0	8.0	4.5	10.0	8.0	4.5
0.047	10.0	8.0	4.5	10.0	8.0	4.5	10.0	9.0	5.0
0.056	10.0	8.0	4.5	10.0	8.0	4.5	10.0	9.0	5.0
0.068	10.0	8.0	4.5	10.0	8.0	4.5	10.0	9.5	5.5
0.082	10.0	8.0	4.5	10.0	8.0	4.5	10.0	9.5	5.5
0.1	10.0	9.0	5.0	10.0	9.0	5.0	10.0	10.0	6.0
0.12	10.0	9.0	5.0	10.0	9.0	5.0			
0.15	10.0	9.0	5.0	10.0	9.5	5.5			
0.18	10.0	9.0	5.0	10.0	9.5	5.5			
0.22	10.0	9.0	5.0	10.0	10.0	6.0			
0.27	10.0	9.5	5.5						
0.33	10.0	9.5	5.5						
0.39	10.0	10.0	6.0						
0.47	10.0	10.0	6.0						
0.56	10.0	11.0	6.5						
0.68	10.0	11.0	6.5						