



# METALIZED POLYESTER FLIM CAPACITOR

## TYPE MEA

### DIMENSIONS:

(unit: mm)

W.V.	125V AC					250V AC				
Cap. ( $\mu F$ )	W	H	T	P $\pm$ 1.0	d $\phi$	W	H	T	P $\pm$ 1.0	d $\phi$
0.010	12.5	9.5	5.5	10.0	0.6	12.5	9.5	5.5	10.0	0.6
0.012	12.5	9.5	5.5	10.0	0.6	12.5	9.5	5.5	10.0	0.6
0.015	12.5	9.5	5.5	10.0	0.6	12.5	10.0	5.5	10.0	0.6
0.018	12.5	9.5	5.5	10.0	0.6	12.5	10.0	5.5	10.0	0.6
0.022	12.5	9.5	5.5	10.0	0.6	12.5	11.0	6.0	10.0	0.6
0.027	12.5	9.5	5.5	10.0	0.6	12.5	11.5	6.5	10.0	0.6
0.033	12.5	9.5	5.5	10.0	0.6	18.0	11.0	6.0	15.0	0.8
0.039	12.5	9.5	5.5	10.0	0.6	18.0	11.0	6.0	15.0	0.8
0.047	12.5	9.5	5.5	10.0	0.6	18.0	12.0	6.5	15.0	0.8
0.056	12.5	9.5	5.5	10.0	0.6	18.0	12.5	6.5	15.0	0.8
0.068	12.5	9.5	5.5	10.0	0.6	18.0	13.0	7.0	15.0	0.8
0.082	12.5	10.0	6.0	10.0	0.6	23.0	12.0	6.5	20.0	0.8
0.10	12.5	10.0	6.0	10.0	0.6	23.0	13.0	7.0	20.0	0.8
0.12	12.5	10.0	6.0	10.0	0.6	23.0	14.0	7.5	20.0	0.8
0.15	12.5	11.0	7.0	10.0	0.6	23.0	15.0	8.5	20.0	0.8
0.18	18.0	11.0	6.5	15.0	0.8	23.0	16.0	9.0	20.0	0.8
0.22	18.0	12.0	7.0	15.0	0.8	23.0	16.5	9.5	20.0	0.8
0.27	18.0	13.0	7.5	15.0	0.8	31.0	17.0	8.0	27.0	0.8
0.33	18.0	14.0	8.0	15.0	0.8	31.0	18.5	9.5	27.0	0.8
0.39	18.0	15.0	8.5	15.0	0.8	31.0	20.0	11.0	27.0	0.8
0.47	23.0	14.0	7.5	20.0	0.8	31.0	21.0	12.0	27.0	0.8
0.56	23.0	14.5	8.0	20.0	0.8					
0.68	23.0	15.0	8.5	20.0	0.8					
0.82	23.0	16.0	9.0	20.0	0.8					
1.0	23.0	17.0	10.0	20.0	0.8					
1.2	23.0	18.0	11.0	20.0	0.8					
1.5	31.0	18.5	10.5	27.0	0.8					
1.8	31.0	20.0	11.0	27.0	0.8					
2.2	31.0	21.0	11.5	27.0	0.8					