



# POLYSTYRENE FLIM CAPACITOR

## TYPE PSI / PST

**DIMENSIONS:**

**(unit: mm)**

W.V.	50V/125V DC			250V DC			630V DC		
Cap. (pF)	OD	L	d φ	OD	L	d φ	OD	L	D φ
56	5.5	12	0.4	5.5	12	0.4	5.5	12	0.4
68	5.5	12	0.4	5.5	12	0.4	5.5	12	0.4
82	5.5	12	0.4	5.5	12	0.4	5.5	12	0.4
100	6.0	12	0.4	5.5	12	0.4	5.5	12	0.4
120	5.5	12	0.4	5.5	12	0.4	5.5	12	0.4
150	5.5	12	0.4	5.5	12	0.4	6.0	12	0.4
180	5.5	12	0.4	5.5	12	0.4	6.0	12	0.4
220	5.5	12	0.4	5.5	12	0.4	6.0	12	0.4
270	5.5	12	0.4	5.5	12	0.4	6.0	12	0.4
330	5.5	12	0.4	5.5	12	0.4	6.5	12	0.4
390	5.5	12	0.4	5.5	12	0.4	6.5	12	0.4
470	5.5	12	0.4	5.5	12	0.4	6.5	12	0.4
560	5.5	12	0.4	5.5	12	0.4	6.5	13	0.4
680	5.5	12	0.4	5.5	12	0.4	6.5	13	0.4
820	6.0	12	0.4	6.5	12	0.4	6.5	13	0.4
1000	6.0	12	0.4	6.5	13	0.4	7.0	13	0.4
1200	6.0	12	0.4	6.5	13	0.4	7.5	13	0.4
1500	6.5	12	0.4	6.5	13	0.4	7.5	13	0.4
1800	6.5	12	0.4	7.0	13	0.4	8.0	13	0.4
2200	6.5	12	0.4	7.0	13	0.4	8.0	13	0.4
2700	7.0	12	0.4	7.0	13	0.4	8.5	13	0.4
3300	7.0	12	0.4	7.5	13	0.4	9.05	13	0.4
3900	7.5	12	0.4	7.0	13	0.4	9.5	13	0.4
4700	8.0	12	0.4	8.0	13	0.4	10.0	13	0.4
5600	8.5	15	0.4	9.0	17	0.4	11.0	13	0.4
6800	9.0	15	0.4	9.5	17	0.4	11.0	13	0.4
8200	9.5	15	0.4	9.5	17	0.4	12.0	20	0.4
10000	10.0	15	0.4	10.5	17	0.4	13.0	20	0.4